

Signal Analysis & Communication ECE 355

Ch. 2.2: CT LTI Systems

Lecture 8

25-09-2023



Ch. 2.2: CT LTI SYSTEMS

- Characterization of CT LTI systems in terms of its (unit) impulse response.


Recall- In DT LTI, the key to developing convolution sum was the sifting property, i.e.,

$$x[n] = \sum_{k=-\infty}^{\infty} x[k] \delta[n-k]$$

any DT sig. can be expressed as $\rightarrow$ Superposition of scaled & shifted impulse functions



- Linearity & time invariance implies that the output to $x[n]$ is:

$$y[n] = \sum_{k=-\infty}^{\infty} x[k] h[n-k]$$


- Similarly, in CT LTI systems:

- The unit impulse response $h(t)$ of a CT LTI system is its output when unit impulse, $\delta(t)$ is the input.



- We can express any sig. using sifting property of $\delta(t)$

$$x(t) = \int_{-\infty}^{\infty} x(\tau) \delta(t-\tau) d\tau$$


any CT sig. can be expressed as $\rightarrow$ integral of scaled & shifted impulse functions

- Linearity & time invariance implies that the output to $x(t)$ is:

$$y(t) = \int_{-\infty}^{\infty} x(\tau) h(t-\tau) d\tau$$

THEOREM: For a CT LTI sys. with impulse response $h(t)$, the output, $y(t)$, to the given input $x(t)$, is:

$$y(t) = \int_{-\infty}^{\infty} x(\tau) h(t-\tau) d\tau \triangleq x(t) * h(t) \quad \text{--- (1)}$$




Examples:

① $x(t) = e^{-at} u(t) \quad (a > 0)$
 $h(t) = u(t)$


$y(t) = ?$

$y(t) = \int_{-\infty}^{\infty} e^{-at} u(\tau) u(t-\tau) d\tau$
from eqn ① above


Step I write/draw $x(\tau) = e^{-a\tau} u(\tau)$



Step II write/draw $h(-\tau) = u(-\tau)$ ($u(\tau)$ flipped)



Step III slide $h(-\tau)$ to the right by 't'



- And check for all the possible different regions of overlap / No overlap of $x(\tau)$ & $h(t-\tau)$ with corresponding different values of 't'.

- For example, in this considered example, we can see the two regions


$t > 0$ Overlap

$t < 0$ No overlap.

Step IV a) - As per the regions of overlap in Step III, multiply $x(\tau)$ & $h(t-\tau)$ & integrate (eqn ①).

b) - For the non-overlapping regions, the product in eqn ① is zero.


a) $t > 0$



$$y(t) = \int_0^t e^{-a\tau} (1) d\tau$$

$$= \frac{e^{-a\tau}}{-a} \Big|_0^t = \frac{1}{a} (1 - e^{-at}) \quad - (2)$$

b) $t < 0$




$$y(t) = 0 \quad - (3)$$

Step IV Epr (2) & (3) $\Rightarrow$

$$y(t) = \begin{cases} 0 & t < 0 \\ \frac{1}{a} (1 - e^{-at}) & t > 0 \end{cases}$$

$$= \frac{1}{a} (1 - e^{-at}) u(t)$$


unit step to
express right
sided sign.



NOTE: If $h(t) = u(t)$, then for any input ranging from $-\infty$ to ∞ :

$$y(t) = x(t) * h(t) = \int_{-\infty}^{\infty} x(\tau) h(t-\tau) d\tau$$

$$= \int_{-\infty}^t x(\tau) d\tau$$




CUMULATIVE INTEGRATION


For example: if $x(t) = \delta(t)$ & $h(t) = u(t)$

$$y(t) = \underbrace{\int_{-\infty}^t \delta(\tau) d\tau}_{= u(t)}$$


(2)



Step I




Step II



Step III

a) (i) $1 < t < 4$




Step IV

Overlap $[0 \rightarrow (t-1)]$

$$y(t) = \int_0^{t-1} (1)(1) d\tau = t-1$$

— (4)


(ii) $4 < t < 6$



Overlap $[(t-4) \rightarrow (t-1)]$

$$y(t) = \int_{(t-4)}^{(t-1)} (1)(1) d\tau = 3 \quad - (5)$$


(iii) $6 < t < 9$



Overlap $[(t-4) \rightarrow 5]$

$$y(t) = \int_{t-4}^5 (1)(1) d\tau = -t + 9 \quad - (6)$$


b) (i) $t > 9$



No Overlap

$$y(t) = 0 \quad - (7)$$

Also, (ii) $t < 1$




No Overlap

$$y(t) = 0 \quad - (8)$$

Step V

Combining Eqs. (4) to (8)


$$y(t) = \begin{cases} 0 & t < 1 \\ t-1 & 1 < t < 4 \\ 3 & 4 < t < 6 \\ -t+9 & 6 < t < 9 \\ 0 & t > 9 \end{cases}$$



REMEMBER: While performing convolution, you should look for all the regions of overlap by sliding $h(-\tau)$ to the right by 't'.

NOTE : If $h(t)$ is a rectangular pulse given as:

$$h(t) = \frac{1}{(b-a)} [u(t-a) - u(t-b)] \quad (a < b)$$




Then for any $x(t)$

$$y(t) = x(t) * h(t) = \frac{1}{(b-a)} \int_{-\infty}^{\infty} x(\tau) [u(t-a-\tau) - u(t-b-\tau)] d\tau$$

For the pulse to exist, i.e., $=1$
 $\begin{cases} (t-a-\tau) > 0 \Rightarrow \tau < (t-a) \\ (t-b-\tau) < 0 \Rightarrow \tau > (t-b) \end{cases}$

$$\Rightarrow y(t) = \frac{1}{(b-a)} \int_{t-b}^{t-a} x(\tau) d\tau$$

AVERAGING.



If Impulse Response, $h(t)$ is a pulse, the output is THE MOVING AVERAGE OF THE INPUT.