

Signal Analysis & Communication ECE 355


Ch. 8.1. Modulation.

Lecture 32.

29-11-2022



Ch. 8. COMMUNICATION SYSTEMS (CS)



- Generally, in all CS, the information at the source is first processed by a transmitter/modulator to change it into a form suitable for transmission over the communication channel.
- At the receiver, the sig. is then recovered through appropriate processing.

Example

- The atmosphere will rapidly attenuate (weakens sig. strength) sig. in the audible freq. range ($10\text{ Hz} \rightarrow 20\text{ kHz}$), whereas it will propagate signals at a higher freq. range over long distances.
- Therefore, to transmit audio sig. over a comm. chr. that relies on propagation through the atmosphere, the transmitter embeds the sig. to higher freq. sig.

↓ This process is called "modulation"

- The modulated sig. is then transmitted through the atmosphere, which is then received at the receiver by extracting the info. bearing sig. through the process of "Demodulation".

- That's the major reason of applying MODULATION, i.e.,

① To embed information into high freq. sig.s that can be transmitted effectively.

NOTE: - If we don't modulate, we would need impractically larger antenna size for longer distance transmission.

- Antenna size is normally $\frac{\lambda}{10} \rightarrow \frac{\lambda}{2}$

where λ is the wavelength of the sig. $\lambda = \frac{c}{f}$

- For the sig. with $f = 10 \text{ kHz}$


$$\lambda = \frac{3 \times 10^8}{10 \times 10^3} = 3 \times 10^4$$

$\therefore$ Req'd. antenna size: $3 \times 10^3 \rightarrow 1.5 \times 10^4 \text{ m}$.
(IMPRACTICAL!)

- Another reason is:

② To make possible the simultaneous transmission of more than one sig. with overlapping spectra over the same channel, through "MULTIPLEXING".

MODULATION



Convention:

$x(t)$: "Baseband signal" / "Modulating signal"

ω_c : "Carrier frequency"

e.g. broadcast radio/TV $\sim$ MHz

WiFi: 2.4/5 GHz

Microwave / Satellite: 1 $\sim$ 300 GHz

$y(t)$: "Passband signal" / "Modulated signal"

Ch. 8.1. AMPLITUDE MODULATION (AM)

- A complex exponential or sinusoidal sig., called carrier sig. with freq. suitable for transmission over the communication channel, has its amplitude multiplied (modulated) by the information bearing sig. $x(t)$.

$$y(t) = x(t) c(t)$$

$\uparrow$
carrier sig.


AM with Complex Exponential Carrier:

- The carrier is a complex exponential of the form:

$$c(t) = e^{j(\omega_c t + \theta_c)} \quad - (1)$$

- For convenience, let $\theta_c = 0$ (ideal)


$$y(t) = x(t) e^{j\omega_c t}$$



- Since the carrier, $c(t)$, is a complex sig., $y(t)$ can be written as:

$$\begin{aligned} \text{eqn ①} \Rightarrow y(t) &= x(t) \cos \omega_c t + j x(t) \sin \omega_c t \\ &= \operatorname{Re}\{y(t)\} + \operatorname{Im}\{y(t)\} \end{aligned}$$

- Therefore, the implementation of eqn ① utilizes two separate multipliers & two sinusoidal carrier signals that have a phase difference of $\pi/2$ (cos & sin).







AM with Sinusoidal Carrier

- In many cases, using a sinusoidal carrier is often simpler & equally effective as using complex exponential carrier.

$$c(t) = \cos(\omega_c t + \theta_c) \quad \text{--- (2)}$$

retaining only
real or imaginary
part.

$$c(t) = \cos(\omega_c t + \theta_c)$$



?

- Assuming, $\theta_c = 0$ (for simplicity/ideal), CTFT of eqn (2) is:

$$C(j\omega) = \pi [\delta(\omega - \omega_c) + \delta(\omega + \omega_c)]$$

$\cos(\omega t) = \frac{e^{j\omega_c t} + e^{-j\omega_c t}}{2}$
 $e^{j\omega_c t} = 2\pi \delta(\omega - \omega_c)$

- For $Y(j\omega)$:


$$y(t) = x(t) c(t)$$

$$Y(j\omega) = X(j\omega) * C(j\omega)$$

$$Y(j\omega) = \frac{1}{2\pi} \int_{-\infty}^{\infty} X(j\theta) C(j(\omega - \theta)) d\theta$$

$$= \frac{1}{2} [X(j(\omega - \omega_c)) + X(j(\omega + \omega_c))]$$

Using sampling property of impulse.




Demodulation (ideal)

- To recover the sig. at the receiver.

- If Am using the carrier given in eqn (1), we want

$$x(t) = y(t) e^{-j\omega_c t} \quad \text{--- (3)}$$

- In freq. domain, this has the effect of shifting the spectrum of the modulated sig. back to its original position on the freq. axis.
- Considering AM using sinusoidal carrier as in eqn(2), to demodulate:



- "Synchronous Demodulation" as we assume $\theta_c = 0$ in both transmitter & receiver.

- In time-domain:

$$y(t) = x(t) \cos \omega_c t \quad \theta_c = 0$$

$$w(t) = y(t) \cos \omega_c t \quad \theta_c = 0$$

$$= x(t) \cos^2(\omega_c t) \quad - (4)$$

$$= x(t) \left(\frac{1}{2} + \frac{1}{2} \cos(2\omega_c t) \right)$$

$$= \frac{1}{2} x(t) + \frac{1}{2} x(t) \cos(2\omega_c t)$$

Pass this part
using LPF with gain 2.

High freq. part
filtered out.

- In freq. domain

$$\text{eqn (4)} \longleftrightarrow K(j\omega) = \frac{1}{2\pi} \int_{-\infty}^{\infty} Y(j\theta) C(j(\omega-\theta)) d\theta$$

$$= \frac{1}{2} [Y(j(\omega-\omega_c)) + Y(j(\omega+\omega_c))]$$

